

# ProfiPress



# PROFIPRESS – THE COMPACT ALL-ROUNDER

The principle behind the development of the PROFIPRESS was to make a robust basic machine which features both solid base equipment and sensible extending option – and all that at a very competitive price.

**The result is something we are proud of.**



## Performance features

Force of Pressure	1350 kN
Working Length max.	3050 mm
Working Length between the Machine Frames	2550 mm
Gap in Frame	305 mm
Table Height overfloor	800 mm
Table Width	90 mm
Stroke of Ram	250 mm
Distance between Table and Ram max.	100 mm
Max. Inclination of Ram, controllable	0-15 mm
Speeds of Strokes: (Y1-Y2-axis)	
Rapid Motion-Down max.	110 mm/sec.
Working Motion max.	10 mm/sec.
Return Motion max.	150 mm/sec.
Connected Load:	
Operating Voltage (any modifications on demand)	3x400V / N / PE / 50Hz
Capacity Main Motor	11 kW
Net Weight approx. (standard mounting)	9100 kg
Dimensions of machine:	
Length:	3500 mm
Width:	1700 mm
Height:	2570 mm
EHT-Standard Colour Painting:	
Combination of:	Light-grey / RAL 7035
Silver-grey – metalleffect	Similar / RAL 7001
Cylinder covering, lateral screens	Signal yellow / RAL 1003